

NM BURS

Full Diamond + Resin Bond

- Good efficiency, no vibrations, low heat build up
- Necessary complement to DUMONT's sintered burs
- Ideal for critical work on delicate ceramic parts
- Very good diamond retention, long lifelength

- Significantly lowers cracking and chipping risks in critical ceramics zones.
- High comfort of utilisation. The resin bond acts as a vibration and choc absorber.

- Recommendations:**
- Speed: 12 to 15.000 RPM, maximum 20.000 RMP
 - **Light pressure, to avoid premature wear out**
 - Re-shaping: 5.000 RPM on wet abrasive green stone (It. 750G)



Diamond
grit

To order, indicate the codes specified hereunder

Ring

Fine (80μ)	7707-050	7745-050	7737-035	7737-050	7738-035	7738-050	7762-035	7762-050	7779-035	7779-050	7709-125	7709-220	Yellow
Medium (110μ)	6807-050	6845-050	6837-035	6837-050	6838-035	6838-050	6862-035	6862-050	6879-035	6879-050	6809-125	6809-220	White
Coarse (160μ)	7807-050	7845-050	7837-035	7837-050	7838-035	7838-050	7862-035	7862-050	7879-035	7879-050	7809-125	7809-220	Red

Hand pieces shanks (2.35mm) only

Retail sales price (unit, in € without taxes, ex Brussels):
22.00 € for 050 diameter ; 20.00 € for 035 diameter